

Gauge **13**

ENDUCTION : NITRILE

CUT RESISTANCE GLOVES



The **+**

- Ultra-high cut protection level
- Oil repellent
- Handling cutting parts in oily environments



**0%
SILICONE**


SIZES	REFERENCES
6	1CRAN06
7	1CRAN07
8	1CRAN08
9	1CRAN09
10	1CRAN10
11	1CRAN11

DESCRIPTION

Knitted Support without seams in HPPE + glass fibres in heather grey, gauge 13.
 Double coating : smooth blue nitrile on the palm and 3/4 back for better protection against oils and fats + black nitrile foam on the palm with textured effect for an excellent holding.
 Maximum level of protection against cuts (level 5/5 according to EN 388).
 Extended shelf life: maximal abrasion resistance and tear resistance (4/4 according to EN 388)
 Elastic cuff for higher protection against dirt.
 Without seams to avoid irritation hazards.
 Not messy colour
 Ideal for manipulations of sharp pieces in oily environment.
 Guaranteed silicone free.

PACKAGING

50 PAIRS / CARTON



APPLICATION DOMAIN

- Logistics
- Waste and recycling
- Sanitation
- Electronic
- Maintenance
- Glass handling
- Wood industry
- Metal handling

STANDARD

CE This glove is in conformity with the model of the individual safety equipment which corresponds to **0075/1747/162/06/17/0900**.
 Delivered by CTC (75)

EN420:2003+A1:2009



EN388:2016

A B C D E
4 X 4 4 D

- Resistance to abrasion (4/4)
- Resistance to blade cut (coupe-test) (X/5)
- Resistance to tear (4/4)
- Resistance to puncture (4/4)
- Resistance to blade cut (TDM) (D/F)