

Gauge **13**

ENDUCTION : NITRILE

CUT RESISTANCE GLOVES



The **+**

- Cut performance and puncture resistance
- Excellent abrasion and tear resistance
- Handling cutting parts



0%
SILICONE

SIZES	REFERENCES
6	1CRVG06
7	1CRVG07
8	1CRVG08
9	1CRVG09
10	1CRVG10
11	1CRVG11

PACKAGING

50 PAIRS / CARTON



X5



X10



DESCRIPTION

Grey knitted support without seams, HPPE, gauge 13.
Black nitrile micro-foam coating on the palm.

- Protection against cuts
- Exceptional grip even for oily pieces manipulation.
- Extended shelf life (great abrasive and tear resistance)
- Maximal tear resistance (4/4 according to EN 388)
- Elastic cuff for higher protection against dirt.
- Without seams to avoid irritation hazards.
- Not messy colour
- Ideal for manipulations of sharp pieces in oily environment.
- Guaranteed silicone free.

STANDARD

EN420:2003+A1:2009



EN388:2016

A B C D E

4 X 4 3 B



- Resistance to abrasion (4/4)
- Resistance to blade cut (coupe-test) (X/5)
- Resistance to tear (4/4)
- Resistance to puncture (3/4)
- Resistance to blade cut (TDM) (B/F)

APPLICATION DOMAIN



Logistics



Transportation



Maintenance



Building



Wood industry



Glass handling



Waste and recycling



Metal handling