

SINGLE USE MASK FFP2 SL VO WITH VALVE

Ref. 23236

TECHNICAL SHEET



MEASUREMENTS

MasK (mm)	139 x 127 x 54 (L x W x H)
Pince-nez (mm)	90 x 5 x 0.5 (L x W x T)
Nose cushion (mm)	139 x 127 x 2 (L x W x T)
Sup. elastic (mm)	540 x 10.5 x 1.5 (L x W x T)
Inf. elastic (mm)	460 x 10.5 x 1.5 (L x W x T)
Valve (mm)	41 x 11 (D x H)
Weight	14 g

GENERAL DESCRIPTION AND MATERIALS

- Single use mask **FFP2 SL**
- Outer layer in **polypropylene**
- Ineer layer in **polyester**
- Filter media : **High Filtration Efficiency Melt-Blown (polypropylene)**
- **Polypropylene and synthetic rubber** valve
- **Carbon** pre-filter against organic vapours
- **Aluminium** pince-nez
- Nose cushion in **foam polyethylene**
- Elastic : sewn elastic band
- Elastic loop in polypropylene

SPECIFIC ADVANTAGES

- Allergic test
- Hygienic
- Expiration valve
- Against organic vapours
- Fire proof
- Waterproofness facial joint

MAIN APPLICATION FIELDS

- Protection against liquid and solid aerosols **up to 12xOEL**
- Against **organic vapours** under OEL
- Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork, welding, melting, metal cutting out, hospitals, laboratories, medical controls
- Against carbonate calcium, china clay, cement, cellulose, sulfur, cotton, flour, carbon, ferrous metals, hardwood, glass fibers, plastic, vegetable oils and mineral oils, quartz, copper, aluminium, bacteria, fungi and mycobacterium tuberculosis (TB)
- **Do not use in a place where oxygen concentration is less than 17 Vol. %**

PACKAGING

- **Individual** packing
- **60 masks** in a box
- 5 masks in an inner box

STANDARDIZATION

This mask is in conformity with the model of individual safety equipment which correspond to

The CE Type-examination certificate 593787

Delivered by **BSI (notified body n° 0086)**

This mask is in conformity with the
« French JO notice » 135 from
06/12/04

EN149 2001+A1 2009



EUROPROTECTION – 420, rue de la Dombes – 01700 MIRIBEL – FRANCE

Tèl. : (33) 04 72 26 23 23 – Fax. : (33) 04 72 26 23 20 – Mail : contacts@europrotection.fr