

MEASUREMENTS

Size	10
Ref.	2525
Total length (mm)	350
Entrance glove width (mm)	130
Palm width (mm)	135
Bar code	3435241025258

GENERAL DESCRIPTION AND MATERIALS

- Palm in grain cow leather
- Split cuff, 15 cm
- Split back
- Superior quality
- Wing thumb
- Pulse guard

SPECIFIC FEATURES

- Flexibility
- Comfort

MAIN APPLICATION FIELDS

- Welding works
- Metallurgical industry
- Protection against heat (up to 100 °C)

PACKING

- Packed by 12 pairs
- **60 pairs** in a carton

STANDARDS


This glove is in conformity with the prototype of personal protective equipment which corresponds to

EC Type-examination certificate N° 0075/108/162/07/10/0301

Issued by **CTC (notified body n° 0075)**

EN 420:2003

EN 388:2003



2122

- **Abrasion** = 2/4
- **Blade cut** = 1/5
- **Tear** = 2/4
- **Puncture** = 2/4

EN 407:2004



41XX2X

- Resistance to **flammability** = 4/4
- Resistance to **contact heat** = 1/5
- Resistance to **convective heat** = X/4
- Resistance to **radiant heat** = X/4
- Resistance to **small splashes of molten metal** = 2/4
- Resistance to **large splashes of molten metal** = X/4

