

# WELDING GLOVE

Ref. 2625

TECHNICAL SHEET



## MEASUREMENTS

Size	10
Ref.	2625
Total length (mm)	360
Entrance glove width (mm)	135
Palm width (mm)	135

## GENERAL DESCRIPTION AND MATERIALS

- Welding glove
- **Split cow leather**
- **Split cuff, 15 cm**
- **Interior : thick lining**

- Thickness : 12/10e
- **Standard quality**
- **Sewing yarn : Kevlar®**
- Fireproof treatment

## SPECIFIC ADVANTAGES

- Comfort
- Interior : thick lining

- **Fireproof treatment**

## MAIN APPLICATION FIELDS

- **Welding jobs**
- Metallurgical industry

- Protects against heat (100 °C)

## PACKAGING

- Packed **by 12**


- **60 pairs** in a box

## STANDARDIZATION

This glove is in conformity with the model of individual safety equipment which correspond to

**The CE Type-examination certificate 0072/108/162/07/96/06342/EXT 03/09/98**

**EN 420 AND  
EN 388:2016**



**3143X**

Delivered by **ITF (notified body n° 0072)**

- **Abrasion** = 3/4
- **Blade cut** = 1/4
- **Tear** = 4/4
- **Puncture** = 3/4
- **Cut resistance TDM** = not tested

**EN 407**



**413X4X**

- Resistance to **flammability** = 4
- Resistance to **contact heat** = 1
- Resistance to **convective heat** = 3
- Resistance to **radiant heat** = X
- Resistance to **small splashes of molten metal** = 4
- Resistance to **large splashes of molten metal** = X

**SACLA** – Z.I. de Rosarge – 01700 LES ECHETS – MIRIBEL – FRANCE

Tél. : (33) 04 72 26 57 57 – Fax. : (33) 04 72 26 51 70 – Mail : [contact@sacla-france.com](mailto:contact@sacla-france.com)