

TECHNICAL DATASHEET

MO2631

Ref. MO2631

Sizes ONE SIZE

SPECIALTIES



DESCRIPTION

Material >> Split cow leather
Cuff >> Split, 15 cm
Interior >> Thick lining
Colour >> Red

SECTORS

Maintenance

Service

Energy

APPLICATIONS EXAMPLES

- Welding,
- Metallurgy,
- Protection against contact heat (100°C for 15 seconds maximum)

WELDING

The +

- Comfort
- Fleece interior

PURCHASE PACKAGING

REF.	SIZES		
2631	10	12	60

PACKAGING

1 Pair / Bag



X1



X5

See also

Variant



MO2630

COVERGUARD

TECHNICAL FEATURES

Fabrics	In split leather red calfskin	Supplement information	Kevlar seams
Linning	Padded interior	Complement cuff	Split leather cuff, length: 15 cm
Type Of Cuff	Safety Cuff	Exterior Finish	Smooth
Construction	Cut and sewn		

INSTRUCTIONS FOR USE AND STORAGE

Instructions for use :

- It is recommended to pre-test the gloves, as the actual conditions of use may differ from those of the "EC" tests. Performance levels are only guaranteed on the palm of the glove when new.
- Wear gloves on dry, clean hands.
- Do not use gloves in contact with a chemical product for longer than the measured permeation time. Refer to the website www.europrotection.com
- In use with a dangerous liquid, turn the cuff edge over to prevent drops from falling on the arm.

Storage instructions :

- Keep gloves away from light, moisture and sources of heat.

Cleaning instructions :

- The washing of the gloves varies according to the materials of the product. See the recommendations on the package leaflet.

LEGISLATION

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate. **8239 Issue 1**. Delivered by **SATRA (321)**.

EN420:2003+A1:2009

- Protective gloves
- General requirements for gloves

EN388:2016



3.1.3.3.X

- Protective gloves against mechanical risks

EN407:2004



4.1.3.1.4.X

- Protective gloves against thermal risks (heat and/or fire)

Retailer stamp