

DISPOSABLE





NITRILE

The 

- Liquidproofness
- Good dexterity
- Comfort and flexibility
- Resistance to mechanical stress and oils



PURCHASE PACKAGING

| REF. | SIZES |  |  |
|------|-------|--|--|
| 5926 | 6 | 100 | 1000 |
| 5928 | 8 | 100 | 1000 |
| 5930 | 9 | 100 | 1000 |
| 5932 | 10 | 100 | 1000 |

PACKAGING

10 BOX100 / Carton



X10

DESCRIPTION

Material >> Nitrile, ambidextrous
Cuff >> Hemmed edge
Length >> 240 mm
Palm thickness >> 0.08 +/- 0.02 mm
Finger thickness >> 0.12 +/- 0.02 mm
AQL >> 1.5

SECTORS

Agricultural industry

Maintenance

Service

APPLICATIONS EXAMPLES

- Object handling, preparation, cooking, paint, solvent, liquid (non-toxic), assembly, cleaning, hospital environments (laboratory), ...

TECHNICAL FEATURES

| | | | |
|---------------------------------|--|---------------------|-------------------|
| Supplement information 3 | Palm thickness (mm) 0.08 +/- 0.02 Finger thickness (mm) 0.12 +/- 0.02 AQL: 1,5 | Construction | Seamless knitting |
| Supplement information 2 | Powder-free non-sterile latex | | |

INSTRUCTIONS FOR USE AND STORAGE

Instructions for use :

- It is recommended to pre-test the gloves, as the actual conditions of use may differ from those of the "EC" tests. Performance levels are only guaranteed on the palm of the glove when new.
- Wear gloves on dry, clean hands.
- Do not use gloves in contact with a chemical product for longer than the measured permeation time. Refer to the website www.europrotection.com
- In use with a dangerous liquid, turn the cuff edge over to prevent drops from falling on the arm.

Storage instructions :

- Keep gloves away from light, moisture and sources of heat.

LEGISLATION

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate. **7806 Issue 2**. Delivered by **SATRA (321)**.

EN420:2003+A1:2009

EN374-1:2003



K(6/6)TYPE C

Retailer stamp