

GLASSES *DUOLUX A*

Ref. 60800

TECHNICAL SHEET



Lux Optical[®]

COLOURS AND MEASUREMENTS

Frame colour	Black
Frame marking	F
Lens options	Welding
Lens marking	5SO 1
Lens standard	EN 169

GENERAL DESCRIPTION AND MATERIALS

- **ABS** frame
- **Adjustable tightening** elastic
- **50 mm diameter** lens
- Protane 5

SPECIFIC ADVANTAGES

- **Adjustable tightening elastic**
- **Separated and removable** lens
- Frame resistant to **low energy impacts**
- Lens **tinted 5** with reinforced solidity
- Optical **class : 1**

MAIN APPLICATION FIELDS

- **Mechanical** protection (industry, building)
- **Welding** protection
- **Dust** protection

PACKAGING

- **Individual** bag
- **25 pairs** in an inner box
- **200 pairs** in a box

STANDARDIZATION

These glasses are in conformity with the model of individual safety equipment which correspond to

The CE Type-examination certificate 0070-108-085-06-07-0062

Delivered by **INRS (notified body n° 0070)**

EN 166



EN 169 for lens

EUROPROTECTION – 420, rue de la Dombes – 01700 MIRIBEL – FRANCE

Tèl. : (33) 04 72 26 23 23 – Fax. : (33) 04 72 26 23 20 – Mail : contacts@europrotection.fr