

GLASSES DUOLUX P

Ref. 60801

TECHNICAL SHEET



Lux Optical[®]

COLOURS AND MEASUREMENTS

Frame colour	Black
Frame marking	F
Lens options	Tinted 5
Lens marking	5 1
Lens standard	En 169

GENERAL DESCRIPTION AND MATERIALS

- **ABS** frame
- **Lateral** ventilation
- **Adjustable tightening** elastic
- **50 mm diameter** lens
- Protane 5

SPECIFIC ADVANTAGES

- **Adjustable tightening elastic**
- **Lateral** ventilation
- Frame resistant to **low energy impacts**
- Lens tinted 5
- Optical **class : 1**
- **Removable lens**

MAIN APPLICATION FIELDS

- **Mechanical** protection (industry, building)
- **Welding** protection
- **Dust** protection

PACKAGING

- **Individual** bag
- **25 pairs** in an inner box
- **200 pairs** in a box

STANDARDIZATION

These glasses are in conformity with the model of individual safety equipment which correspond to

The CE Type-examination certificate N°I/IST.MASINI/159/95 REV.1

Delivered by **ISTITUTO DI RICERCHE E COLLAUDI (notified body n° 0068)**

EN 166



EN 169 for lens

EUROPROTECTION – 420, rue de la Dombes – 01700 MIRIBEL – FRANCE

Tèl. : (33) 04 72 26 23 23 – Fax. : (33) 04 72 26 23 20 – Mail : contacts@europrotection.fr