




WORK POSITIONING LANYARD 2.0 M WITH RING TYPE ADJUSTER+ 2 connectors

Ref. 71245

TECHNICAL SHEET

CE 0321



tested as per EN 358, 1999

Gencode :
3435241 712455

GENERAL DESCRIPTION AND MATERIALS

- Polyamide weaved rope
- Rope Diameter : 12 mm
- Maximum Length : 2.0m
- Static strength: > 15KN
- 2 loops, one is adjustable
- Weight : 725 g (+/-10%)
- Breaking strength minimum : 22KN

SPECIFIC ADVANTAGES

- Braided rope with ring type adjuster
- 1 adjustable loop
- Delivered with 2 connectors 71110

MAIN APPLICATION FIELDS

- Job in **high places** in combination with a **fall arrestor system** or a **work positioning system**.
- **Caution** : a lanyard without an energy absorber shall not be used within a fall arrestor system
- **Construction and civil engineering**
- Dynamic strength: **mass of 100Kg maximum**
- **Attachment** between this lanyard and any other equipment or anchorage point shall only be carried out with connectors in accordance with EN 362.

PACKAGING

- Individual packing
- Carton of 20 lanyard

STANDARDIZATION

This rope is in conformity with the model of individual safety equipment which correspond to **EN 358:1999** The CE Type-examination certificate 2789 Issue 4 Extension 1

Delivered by **SATRA (notified body n° 0321)**



EUROPROTECTION – 420, rue de la Dombes – 01700 MIRIBEL – FRANCE