

MULTIPURPOSE


HIGH SHOES

S3 SRC

The +

- Padding for snug fit.
- Wide range of sizes (2 to 13.5).

PURCHASE PACKAGING

REF.	EU	US	
9AGAH34	34	2.5	10
9AGAH35	35	3	10
9AGAH36	36	4	10
9AGAH37	37	4.5	10
9AGAH38	38	5.5	10
9AGAH39	39	6	10
9AGAH40	40	7	10
9AGAH41	41	8	10
9AGAH42	42	8.5	10
9AGAH43	43	9.5	10
9AGAH44	44	10	10
9AGAH45	45	11	10
9AGAH46	46	11.5	10
9AGAH47	47	12.5	10
9AGAH48	48	13.5	10
9AGAH49	49	14	10



DESCRIPTION

S3 SRC shoes - Steel toecap - Antipenetration steel sole - External sole in double density PU/PU - Upper in leather - Lining in breathable and non-woven fabric - Padded collar for more protection and more comfort - Antislidding outsole on ceramic and steel floor - Outsole resistant to hydrocarbons - Antistatic outsole - Energy absorbing heel

SECTORS

Service

Second work

Infrastructure, building industry

Transport and logistics

APPLICATIONS EXAMPLES

- Luggage handler,
- Delivery driver, ...

See also

Variant



9AGAL

TECHNICAL FEATURES

Closure	Lacing	Anti perforation sole	Stainless less
Toe cap	Steel	Padding	Padded bracelet
Examples of applications	Luggage handler, Delivery driver, ...	Color	Black
Upper	Top grain leather	Insole	Removable, textile and foam
Loops	Metal eyelets	Midsole	Injected polyurethane
Wearing sole	Polyurethane	Main assembly	Injected assembly
Lining	Moisture wicking non-woven		

INSTRUCTIONS FOR USE AND STORAGE

Instructions for use :

- These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions :

- Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Cleaning instructions :

- Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

LEGISLATION

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100370582**. Delivered by **INTERTEK (362)**.

EN ISO 20345:2011

S3 SRC

S3 : A 200 Joule impact and 15 000 Newton compression resistant toe-cap / Closed heel / Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ / Fuel and oil resistant contact outsole / Energy absorbing heel $E \geq 20$ Joules / Puncture resistant midsole : resistant to a 1 100 Newtons pressure / Water penetration and absorption resistant upper / Spiked outsole
SRC : Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

PPE CAT. II

Major risks

Retailer stamp