

Occupational footwear AGO Low

Ref. 9AGOL



Standards: 01
FO
SRC

Average weight: 500g



SIZES

Sizes	36	37	38	39	40	41	42
Ref.	9AGOL36	9AGOL37	9AGOL38	9AGOL39	9AGOL40	9AGOL41	9AGOL42
Gencode	3435249033361	3435249033378	3435249033385	3435249033392	3435249033408	3435249033415	3435249033422
Sizes	43	44	45	46	47	48	-
Ref.	9AGOL43	9AGOL44	9AGOL45	9AGOL46	9AGOL47	9AGOL48	-
Gencode	3435249033439	3435249033446	3435249033453	3435249033460	3435249033477	3435249033484	-

GENERAL DESCRIPTION AND MATERIALS

- Without protection
- This shoe is not an individual protection equipment
- Dual density polyurethane sole
- Synthetic rubber lining
- Non woven inner lining
- Synthetic felt insole
- Black grain buffalo leather upper
- White synthetic felt lining
- Black padded full grain cow leather tongue

Outsole slip resistance

SRC = conformity SRA and SRB

Floor	Ceramic / detergent (SRA)	Steel / glycerol (SRB)
Heel part	conformity ≥ 0.28	conformity ≥ 0.12
Flat contact	conformity ≥ 0.32	conformity ≥ 0.16

Occupational footwear AGO Low

Ref. 9AGOL



SPECIFIC ADVANTAGES

- Thick sole
- Sole conforming **SRC**
- **Oil and hydrocarbons resistant sole**
- High slip resistance on ceramic floor
- **Energy absorbing heel**
- **Anti-static sole**

MAIN APPLICATION FIELDS

- Sliding places
- Petroleum industries
- Working places without falling risks, collision or sole perforation

PACKAGING

- **Individual box**
- **10 pairs in a box**

STANDARDIZATION

This shoe is in conformity with the model of the individual safety equipment which corresponds to

The CE Type-Examination certificate LECFT00331653

Delivered by **INTERTEK (notified body n° 0362)**

EN ISO 20347:2011

CLASSE 01 FO SRC



01

FO

SRC

Standard's protections :

- Closed back
- **Anti-static properties**
- **Energy absorbing heel**
- Oil resistant sole
- **Anti-slip sole**

