

OUTDOOR

HIGH SHOES

S3

WR

SRC


### The +

- Water repellent.
- Padded collar, ankles and bellows tongue for snug fit.
- Footbridge supplying torsional rigidity.

0%  
METAL



#### PURCHASE PACKAGING

REF.	EU	US	
9AQUA38	38	5.5	10
9AQUA39	39	6	10
9AQUA40	40	7	10
9AQUA41	41	8	10
9AQUA42	42	8.5	10
9AQUA43	43	9.5	10
9AQUA44	44	10	10
9AQUA45	45	11	10
9AQUA46	46	11.5	10
9AQUA47	47	12.5	10

#### DESCRIPTION

Breathable composite toecap  
 Antipenetration textile sole  
 External sole in double density PU/PU  
 Upper in crazy horse leather  
 Lining : Waterproof membrane  
 Reinforcement : front and back in PU  
 705 g per shoe in size 8

#### SECTORS

Mining

Energy

Infrastructure, building industry

Extracting Oil And Gas

#### APPLICATIONS EXAMPLES

- Builder,
- Slater,
- Ramp agent,
- Luggage handler,
- Site supervisor,
- Docker, ...

## TECHNICAL FEATURES

<b>Closure</b>	Lacing	<b>Anti perforation sole</b>	Textile
<b>Toe cap</b>	Composite	<b>Reinforced part of shoe</b>	Footbridge supplying torsional rigidity
<b>Bootstrap</b>	At the back	<b>Padding</b>	Padded gussets bracelet, ankle and tongue
<b>Examples of applications</b>	Builder, Slater, Ramp agent, Luggage handler, Site supervisor, Docker, ...	<b>Toecap (2)</b>	Breathable toe cap
<b>Color</b>	Black/Blue	<b>Upper</b>	Full grain leather
<b>Insole</b>	Removable, textile and foam	<b>Loops</b>	Metal hooks
<b>Midsole</b>	Injected polyurethane	<b>Wearing sole</b>	Polyurethane
<b>Main assembly</b>	Injected assembly	<b>Lining</b>	Moisture wicking non-woven and waterproof membrane

## INSTRUCTIONS FOR USE AND STORAGE

### Instructions for use :

- These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

### Storage instructions :

- Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

### Cleaning instructions :

- Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## LEGISLATION

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100341290**. Delivered by **INTERTEK (362)**.

EN ISO 20345:2011

**S3** **WR** **SRC**

**S3** : A 200 Joule impact and 15 000 Newton compression resistant toe-cap / Closed heel / Antistatic shoe  $0,1M\Omega < A < 1000 M\Omega$  / Fuel and oil resistant contact outsole / Energy absorbing heel  $E \geq 20$  Joules / Puncture resistant midsole : resistant to a 1 100 Newtons pressure / Water penetration and absorption resistant upper / Spiked outsole

**WR** : Water repellent shoe

**SRC** : Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

PPE CAT. II

Major risks

Retailer stamp