

Ref. **9LEAL**

Indoor

Low

Low shoes



### The +

- \*Compatible with ESD Protected Areas
- \*Comfort and lightweight
- \*Excellent grip

#### PURCHASE PACKAGING

Référence	Taille	Carton
9LEAL36	36	10
9LEAL37	37	10
9LEAL38	38	10
9LEAL39	39	10
9LEAL40	40	10
9LEAL41	41	10
9LEAL42	42	10
9LEAL43	43	10
9LEAL44	44	10
9LEAL45	45	10
9LEAL46	46	10
9LEAL47	47	10
9LEAL48	48	10

#### DESCRIPTION

Light shoes thanks to its composite toecap and antipenetration textile sole Antislidding outsole on ceramic and steel floor Outsole resistant to hydrocarbons Antistatic outsole Energy absorbing heel Light and flexible Additional pair of yellow laces delivered with the shoes Outsole resistant to hydrocarbons Antistatic outsole Energy absorbing heel Light and flexible

#### SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

#### APPLICATIONS

Painter,  
Electrician,  
Storekeeper, ...

## TECHNICAL FEATURES

<b>Color</b>	Grey	<b>Main assembly</b>	Injected
<b>Color 2</b>	Blue	<b>Closing</b>	Lacing closure
<b>Upper</b>	Suede leather / Mesh	<b>Lining</b>	Breathable 3D mesh
<b>Toecap</b>	Composite		
<b>Puncture resistant sole</b>	Textile		
<b>Midsole</b>	PU		
<b>Outsole</b>	PU		
<b>Insole</b>	Removable, textile and cushioned foam		

## INSTRUCTION FOR USE AND STORAGE

**Instructions for use**

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructions**

Place the shoes, when not in use, in a dry, clean and airy place. The tim influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructions**

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00364327**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom

**EPI CAT. II****EN ISO 20345:2011****S1P**

Safety shoes

**S1P** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe  $0,1M\Omega < A < 1000 M\Omega$  + Fuel and oil resistant contact outsole + Energy absorbing heel  $E \geq 20$  Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

**SRC**

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

**ESD**

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

RETAILER STAMP