

OUTDOOR

DESCRIPTION

Composite toecap
Antipenetration textile sole
External sole in double density PU/Rubber
Upper in crazy horse leather
Lining : Waterproof membrane
Reinforcement: front and back in TPU

SECTORS

Mining

Energy

Infrastructure, building industry

Extracting Oil And Gas

APPLICATIONS EXAMPLES

- Builder,
- Slater,
- Ramp agent,
- Luggage handler,
- Site supervisor,
- Docker, ...

HIGH SHOES




The +

- Heel and toe scuff caps for a longer shoe's lifespan.
- Footbridge supplying torsional rigidity.
- Defined heel for better safety especially on ladders.



PURCHASE PACKAGING

REF.	EU	US	
9TERR38	38	5.5	10
9TERR39	39	6	10
9TERR40	40	7	10
9TERR41	41	8	10
9TERR42	42	8.5	10
9TERR43	43	9.5	10
9TERR44	44	10	10
9TERR45	45	11	10
9TERR46	46	11.5	10
9TERR47	47	12.5	10



TECHNICAL FEATURES

Closure	Lacing	Anti perforation sole	Textile
Toe cap	Composite	Heel	Raised heel
Reinforced part of shoe	Footbridge supplying torsional rigidity Heel and toe scuff caps	Bootstrap	At the back
Examples of applications	Builder, Slater, Ramp agent, Luggage handler, Site supervisor, Docker, ...	Color	Brown/Black
Upper	Full grain leather	Insole	Removable, textile and foam
Loops	Plastic hooks	Midsole	Injected polyurethane
Wearing sole	Nitrile rubber	Main assembly	Injected assembly
Lining	Breathable 3D mesh and waterproof membrane		

INSTRUCTIONS FOR USE AND STORAGE

Instructions for use :

- These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions :

- Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Cleaning instructions :

- Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

LEGISLATION

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100348099**. Delivered by **INTERTEK (362)**.

EN ISO 20345:2011

S3 **HRO** **WR** **HI** **SRC**

S3 : A 200 Joule impact and 15 000 Newton compression resistant toe-cap / Closed heel / Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ / Fuel and oil resistant contact outsole / Energy absorbing heel $E \geq 20$ Joules / Puncture resistant midsole : resistant to a 1 100 Newtons pressure / Water penetration and absorption resistant upper / Spiked outsole

HRO : Heat contact resistant outsole (60 seconds at 300°C)

WR : Water repellent shoe

HI : Shoe insulation against heat (30 minutes at 150°C)

SRC : Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

PPE CAT. II

Major risks

Retailer stamp